Rototherm

Def Stan
Pressure Gauges
Aluminium Solid
Front Model SPGA

Our SPGA Pressure Gauges are designed for accurate pressure measurement with a reliable, robust design and built for industrial purposes. Also available according to Defence Standard 66/2.

General Specification

Nominal Size:	63mm, 100mm and 150 mm
Case:	Aluminium case painted black, solid front and blow out back or painted in admiralty grey for Def Stan 66/2
Dial:	Aluminium, black lettering on white to EN837-1
Window:	Safety Glass or Electrical Contact Head
Mounting:	Direct mount (bottom entry) / Direct mount (rear entry) / Surface mount (direct entry) / Panel Mount (rear entry)
Filling:	Non-fillable
Pointer:	Aluminium black. Standard or Micro-Adjustable
Wetted Parts:	AISI 316 Stainless Steel block & bourdon tube or Monel to NACE MR-01-75
Movement:	AISI 304 Stainless Steel
Ranges:	From -1 to 1000 BAR
Connections:	1/2" BSP or NPT, 3/8"BSP and 1/4" BSP or NPT for 63 mm
Accuracy:	Class 1.0 (±1.0%FSD) for 100 and 150 mm/ 1.6% (±1.6%FSD) for 63 mm / 0.5%
Over Range Protection:	1.3 x FSD (130%)
Safety Pattern Designation:	Full Safety Pattern to European Standard EN837-1 (S3)
Ingress Protection:	IP65 as per EN 60 529 / IEC 529
Ambient Temperature:	-40°C to +60°C
Process Temperature:	+200°C max
Weight:	Up to 1 kg.
_	



Def Stan 66/2 SPGA Model

For other options, please contact us Sales@rototherm.co.uk or +44 (0)1656 740551

Extras: Oxygen Clean and SS Tags

Main Applications

A **world leader** in pressure gauges, Rototherm has become the standard for accurate and reliable measurement across the following industries:



Defence On/Offshore Environments



Power Stations



Chemical & Petrochemical



Plant Construction

www.rotothermgroup.com rototherm@rototherm.co.uk (UK) +44 1656 740551

Kenfig Industrial Estate, Margam, Port Talbot SA13 2PW United Kingdom



Series 300 Pressure Switch

Technical Certification

- · Certificate of conformity
- Factory Test Certificate
- Factory Calibration Certificate (3 point)
- Factory Calibration Certificate (5 point)
- Material Certificate

Export Documentation

- Certificate of Origin
- EUR1
- ATR

Calibration and After-Sales Support

- Fully trained field service personnel
- Use of UKAS certified calibration equipment
- 5 day turnaround
- Fixed pricing
- Approved manufacturer parts
- Full post-service reports
- 12 month warranty



ISO9001:2015 FM11958



For more information, please contact our service team services@rototherm.co.uk

